








# ELISSA ALIZY TRG TO-4 SAE 30

## HYDRAULIC TRANSMISSION OIL SEMI-SYNTHETIC

-  ALL-SEASON OIL
-  RESISTANT "PROTECTIVE COAT"
-  HIGH VISCOSITY INDEX
-  HIGH PERFORMANCE PROPERTIES
-  ENERGY-SAVING AND RESOURCE EFFICIENT

ELISSA ALIZY TRG TO-4 SAE 30 is a multi-purpose, all-season lubrication fluid based on synthetic components. It is recommended to use it in power transmissions, hydraulic systems, oil-immersed brakes and clutches, as well as in power take-off units and inboard transmission. It is suitable for use in cranes, loaders, special quarry or off-road machinery, dump trucks and tractors where TO-4 oils are necessary. This oil is not intended for use in machines that require lubrication with UTTO oil.

The oil is better adapted to low temperatures and ensures possibility of extended oil change periods in comparison to mineral-based oils.

### ADVANTAGES


- compatible with packers and non-ferrous metals and securely protects them;
- has perfect neutralizing capacity and prevents wearing, corrosion and deposits (lacquer, sticky and other);
- optimal friction characteristics decrease friction and wear on surfaces, it ensures reliable operation of brakes and clutch;
- excellent cold characteristics decrease possibility of unplanned downtimes;
- its versatility helps to avoid confusion and to decrease expenditures for buying of lubricants range;
- its operational characteristics exceed requirements of most of similar products from Russian and international manufacturers.

### RECOMMENDED FOR

- Loaded transmissions and the transmissions of off-road, construction and agricultural machinery.
- Off-road vehicles that require TO-4 grade oils.
- Use in power transmissions, oil-immersed brakes and clutches, as well as in power take-off units and inboard transmissions.
- Use in extremely harsh operating conditions.
- Not intended for use in machines that require lubrication with UTTO grade oil.



### PHYSICAL AND CHEMICAL INDICATORS

	<b>154</b>
	<b>6,6</b>
	<b>212</b>
	<b>-33</b>
	<b>1,3</b>
	<b>0,869</b>
	<b>12,6</b>

### CONFORMS TO THE REQUIREMENTS OF

API GL-4, CF/CF-2 | SAE 30

CAT TO-4 | KOMATSU KES 07.868.1 | ZF TE-ML 03C, 07F | ALLISON C-4

### QUALITY LEVEL

STO 06472266-006-2019 "Hydraulic transmission semi-synthetic oil"